

# battery bank®

PRODUCT: 230V 16A 11 DOOR SITE CHARGING UNIT  
PART NO.: S10401

TF/S10401/1.12.01 Iss. 01 Iss. Date 18/04/06

Battery Bank has been designed to provide a safe environment for charging power tool batteries. A patented locker system with 20 integral RCD protected power points.

Battery Bank offers 10 charging lockers each utilising a coin return lock. Within each charging locker there is a 2 gang RCD protected socket.

## SPECIFICATIONS & TECHNICAL DATA

- **INPUT VOLTAGE** 230V~
- **AMPERAGE** 16A
- **FREQUENCY** 50Hz
- **PLUG** Defender 230V 16A  
(manufactured to BS EN 60309)
- **CABLE** 3M 3G1.5mm<sup>2</sup> H07 RNF  
(manufactured to BS6500)
- **COLOUR** Red doors & Grey body
- **DIMENSIONS** 1880 x 460 x 305mm (overall)  
270 x 200 x 280mm (charging lockers)  
270 x 420 x 280mm (management lockers) (H x W x D)
- **COIN OPERATION** £1 coin only to operate the door locks.
- **MAXIMUM OUTPUT PER SOCKET** 0.8A (800mA) per socket.  
Typical 24V single battery charger 500mA, mobile phone chargers 100-200mA.
- **WEIGHT** 63Kg
- **VARIANTS** 11 Door locker only.

