PRODUCT SPECIFICATION SHEET



CRHD950CF

950WATT SDS+ ROTARY PNEUMATIC HAMMER DRILL







SPECIFICATIONS	
Input Power:	950 W
No Load Speed:	0-1000 RPM
Number of Impacts:	0 – 4800 BPM
Chuck Type (Fitted):	SDS-Plus
Maximum Drill Capacity in Wood:	40 mm
Maximum Drill Capacity in Steel:	13 mm
Maximum Drill Capacity in Masonry:	26 mm
Tool Weight:	4.0 kg
Joules:	2.3 J
Weight:	4.0 kg

FEATURES	
Powerful 950 Watt Motor:	To comfortably tackle the most demanding concrete drilling and chiselling applications
Magnesium & Carbon Fibre Construction:	Offers the ultimate in superior strength, durability and lighter weight
Rotary Pneumatic Hammer Action:	Delivering 2.3J for rapid efficient drilling and chiselling into brick and concrete
4 Modes of Operation:	Select from 4modes of operation, Rotation Only (drilling), Rotary Hammer with Rotation (hammer drilling) and Stop Rotation Fixed Rotation – (Hammer Action for tile lifting) – Stop Rotation with Free Rotation (chiselling)
SDS–Plus Bit System:	For tool free bit changes with automatic bit locking, dust protection and maximum impact energy transfer rate
Includes Keyed Chuck Adaptor:	Allows the supplied 13mm chuck included to be fitted allowing the use of straight shank drill bits and accessories for NON Hammer applications only
Super Compact Design:	Ideal for extended use and tight work spaces
360° Adjustable Auxiliary Side Handle:	Allows two handed operation with the side handle in the most convenient position to suit the operator and the task
Rubber Grip:	For improved comfort and control

STANDARD EQUIPMENT
13mm Keyed Chuck With Key (Suitable for NON Hammer Drilling Only)
Grease Pot
Depth Guage Rod
Auxiliary Handle
Carry Case