

PRODUCT SPECIFICATION SHEET



1400W 210MM SLIDE COMPOUND MITRE SAW WITH LASER LINE GENERATOR | LSMS210A



L A S E R G U I D E

| SPECIFICATIONS | |
|----------------------------------|-------------|
| Input Power: | 1400 W |
| No Load Speed: | 5000 RPM |
| Blade Size: | 210 mm |
| Bore Size: | 30 mm |
| Blade Teeth: | 24 TCT |
| Bevel Cut at 45° x 90°: | 200 x 34 mm |
| Compound Mitre Cut at 45° x 45°: | 140 x 34 mm |
| Mitre Cut at 90° x 45°: | 140 x 60 mm |
| Straight Cut at 90°: | 200 x 60 mm |
| Spindle Lock: | Yes |

| FEATURES | |
|---|--|
| Laser Line Generator: | For improved cutting vision, faster set-up, increased accuracy and safer operation |
| Dual Laser Line: | Allows fast, accurate setting to both sides of the saw blade ensuring greater visibility of the cutting line |
| Powerful 1400 Watt Motor: | The power to handle tough timbers and severe cutting tasks |
| Double Bar Slide System: | For an extended cutting capacity and greater accuracy |
| Mitre Cuts from 0° to 52° Left and Right: | Allowing a full range of mitre cuts |
| Positive Mitre Table Stops: | Allows fast and convenient setting of common mitre cuts |
| Bevel Cuts from 0° to 45°: | Enables a complete range of bevel and compound mitre cuts |
| Strong Robust Alloy Construction: | For greater strength and durability |
| D-handle Design with Rubber Grip: | For improved ergonomics and greater comfort |
| Adjustable Depth of Cut: | Permits trench cutting for greater versatility |
| Spindle Lock Button: | Allows quick and easy blade changes |
| Dust Extraction Port: | For a cleaner and safer working environment |
| Lock Down Facility: | For portability and ease of storage |
| Carbide Tipped Saw Blade: | Stays sharper longer for an extended service life |

| STANDARD EQUIPMENT |
|-------------------------|
| 210mm 24T TCT Saw Blade |
| Workpiece Clamp |
| 6mm Hex Key |
| Side Support Bars x2 |
| Dust Bag |