

SPIT PULSA 65



In accordance to:
 EN 15895-1
 EN ISO 8662-11
 Directive tool :
 2012/19/EC
 2011/65/EC
 2006/42/EC
 2004/108/EC
 1999/5/EC
 Aerosol Dispenser Directive: 75/324/EC
 Battery:2006/66/EC
 Charger:2014/35/EU
 CEM 2014/30/EU

Tool Specifications

Name	SPIT PULSA 65
Impact force (Joules)	107
Weight (kg)	4.1 (with battery)
Overall dimension LxH (mm)	404x113x362
Energy	Fuel cell & Battery
Fastener lengths (mm)	15 to 65 mm in strip

Characteristics

Drywall pin guide
Fully automatic tool (1000 shots per hour)
30 pins magazine (10 per strip)
Low push down force (4.5 kg)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Automatic gas dosage (used T° - 15 °C to + 49 °C)
Battery charging time: 105 mn (25 mn = 1000 pins)
Fuel cell: 600 shots (20 °C), battery: up to 10000 shots

Safety Specifications

CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 15895-1 : LpA,1s,1m=95dB(A) / Lp Cpeak=135 dB
Vibration, EN ISO 8662-11: 4.4 m-s ⁻²

Accessories	Consumables
30 pins magazine	C6, HC6,UP6
Cleaning kit	