



## Applications

Sheathing to wood, sheathing to steel, wood decking, composite decking, rigid foam insulation, cement board, underlayment and flooring, drywall to wood, drywall to steel, fiberglass backed gypsum sheathing, metal framing, structural steel decking

## Features & Benefits


- Patented corner-fit feed system  
Detachable feed system to expose bit for quick reversing  
Selectable 2500/1600 RPM high torque brushless motor  
Precise depth of drive adjustment with depth lock  
Quick slide button bit change  
Variable speed trigger with lock and reverse

## Duraspin Screwdriver

### Technical specifications

Dimension (LxWxH)	419,5x86x241 mm
Net weight	2,7 kg
Sound pressure level (Lpa)	63,5 dB
Sound power level (Lwa)	74,5 dB
Vibration level	1,1 m/s <sup>2</sup>
Magazine capacity	50 pieces
Battery type	Li-Ion
Battery voltage	18 V
Battery ampere rating	3 Ah
Battery power	54 W
Recharge time 80%	15 minutes
Recharge time 100%	45 minutes
Shots per charge	2000
Number of batteries in kit	2 pieces
Voltage (ac)	230 V
Frequency	50 Hz
Electrical plug type	UK
Rotations per minute (RPM)	2500 RPM

### Fastener specification



### Description

DS722-18V, DuraSpin Screwdriver

### Art. Nr.

10C7001N

### EAN code

8715274245171