















## **Applications**

Fastening haften onto wood on roofs, tin roofs, zinc sheathing and covering. Great for any application where cordless convenience would be a benefit.


## **Features & Benefits**

- Cordless convenience no hoses, no compressors, no hassles. Navigate the job site with no restrictions
- Powerful motor high-voltage ignition gives you more power and cleaner combustion
- Consistent drives in all weather conditions performs optimally between -7° to 49°C
- Durable metal magazine rugged design outlasts plastic
- Tool-free, metal thumbwheel depth-of-drive

   easily control fastener depth with no tool required

Technical specifications	
Dimension (LxWxH)	327x137x310 mm
Net weight	2,48 kg
Firing mode	Restrictive
Operating temperature range	-7 - 49 °C
Sound pressure level (Lpa)	95,8 dB
Sound power level (Lwa)	97,8 dB
Vibration level	1,84 m/s <sup>2</sup>
Shots / second	2
Magazine capacity	36 pieces
Collation type 1	Plastic collated
Collation angle	20 °
Battery type	Li-Ion
Battery voltage	7,2 V
Battery ampere rating	2,5 Ah
Recharge time 100%	120 minutes
Shots per charge	8000
Number of batteries in kit	2 pieces
Fuel cell type	18 gram
Shots per fuel cell	1200
Voltage (ac)	230 V
Frequency	50 Hz
Electrical plug type	UK

## **Fastener specification**



DescriptionArt. Nr.EAN codeGT35i-HN, haften nailer12VS7001N8715274246956