



Applications

Fastening joist hangers, seismic and hurricane ties, rafter ties, post bases and caps, foundation anchors, and other metal framing hardware.

Features & Benefits


- Full comfort grip - Resilient grip reduces fatigue
- Long service life battery
- Stowable belt hook - keeps tool close at hand
- Rear two step loading - quick and easy for right or left handers
- Depth of drive - for precise depth control
- Rear loading - Quick and easy for right or left hander's
- High voltage ignition - For more power and cleaner combustion
- Dry fire lock-out
- Nail guide mechanism - overhanging nail tip for locates pre-punched hols

Metal connector nailer

Technical specifications

Dimension (LxWxH)	425x108x393 mm
Net weight	4,02 kg
Firing mode	Restrictive
Sound pressure level (Lpa)	101 dB
Sound power level (Lwa)	107 dB
Vibration level	2,28 m/s ²
Fastener driving power	85 J
Magazine capacity	24 pieces
Collation type 1	Plastic collated
Collation type 2	Paper collated
Collation angle	34 °
Battery type	Li-Ion
Battery voltage	7,2 V
Battery ampere rating	2,5 Ah
Recharge time 100%	120 minutes
Shots per charge	8000
Number of batteries in kit	2 pieces
Length fuel cell	165 mm
Fuel cell type	40 gram
Shots per fuel cell	1000
Voltage (ac)	230 V
Frequency	50 Hz
Electrical plug type	UK

Fastener specification



Description

GT60i-NN, metal connector UK

Art. Nr.

14VS7001N

EAN code

8715274246970