



## Applications

Sheathing, furniture framing, roof decking, subflooring, crate and box assembly, pallets, cedar shingles, furring, metal tie-down straps, fascia and soffits, and ridge beam assembly

## Features & Benefits

- Durable construction
- Driver has high-strength rib design, threaded piston/driver connection, and aluminum cylinder sleeve. Minimizes downtime and operating costs
- Multi-directional stitching at up to 14 staples per second
- Lightweight and compact with excellent balance and an impressive power-to-weight ratio
- Adjustable depth of drive for consistent and controllable staple set
- EZ-Clear latch provides quick and easy clearing of occasional jams
- Ergonomic comfort grip handle
- Quiet operation with adjustable exhaust for user comfort
- Reload indicator lets user know it's time to add more fasteners

## Description

SNS41-N, hw stapler, dual

## Art. Nr.

3L2003N

## EAN code

0741474308161


# Heavy wire stapler

## Technical specifications

Dimension (LxWxH)	381x75x273 mm
Net weight	2,1 kg
Firing mode	Dual
Air inlet	3/8" female NPT
Operating pressure	5,5 - 8,3 bar
Air consumption (at 60 shots per minute)	153 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	84 dB
Sound power level (Lwa)	92 dB
Vibration level	2,5 m/s <sup>2</sup>
Shots / second	12
Magazine capacity	160 pieces
Gauge	16 ga.
Collation type 1	Glue collated
Collation angle	0 °

## Fastener specification

**N staple**  
10,6 mm



**O staple**  
10,6 mm

