

SENCO[®]MAKING HARD WORK
EASIER

Applications

For upholstery operations and varied component assemblies in furniture manufacturing, such as drawers, casebacks, cabinet frame assembly, and upholstery spring attachment. Used in underlayment sheathing, paneling, molding/trim, soffits, pre-finished gypsum, and siding for on-site and manufactured housing, lattice and bed-spring attachment

Features & Benefits


- Lightweight for ease of handling
- Ergonomically designed with a comfort-grip handle to reduce fatigue
- Adjustable depth-of-drive for precise staple setting
- Fewer moving parts for less maintenance and minimal downtime
- No-mar pad keeps work surfaces free of marks
- Oil-free design means easier maintenance and no lubrication to stain fine wood
- Muffler ensures quiet operation

Medium wire stapler

Technical specifications

Dimension (LxWxH)	305x51x216 mm
Net weight	1,13 kg
Firing mode	Dual
Air inlet	1/4" female NPT
Operating pressure	4,8 - 8,3 bar
Air consumption (at 60 shots per minute)	54,4 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	80 dB
Sound power level (Lwa)	87 dB
Vibration level	2,5 m/s ²
Fastener driving power	14,2 J
Shots / second	10
Magazine capacity	168 pieces
Gauge	18 ga.
Collation type 1	Glue collated
Collation angle	0 °

Fastener specification



Description

SLS20XP-M, mw stapler, case

Art. Nr.

492024N

EAN code

0741474040276