



Applications

Upholstering operations, furniture assembly, cabinets, automotive vinyl roofs and interior trim, bedding manufacture, TV and stereo grill cloth, picture frames, shoe making, molding, house wrap, and roofing felt.

Features & Benefits


- Full 25,4mm lip length - makes getting into tight spots easier
- Rounded steel cap - won't snag fabric
- Lightweight and balanced at 950 gram.
- Rear magazine bumper - protects fabric
- Comfort grip - reduces fatigue
- Rear exhaust – Directs oil and dust away from work surface

Light wire stapler

Technical specifications

| | |
|--|----------------------|
| Dimension (LxWxH) | 241x49x151 mm |
| Net weight | 0,95 kg |
| Firing mode | Restrictive |
| Air inlet | 1/4" female NPT |
| Operating pressure | 4,1 - 6,5 bar |
| Air consumption (at 60 shots per minute) | 21,8 l/m |
| Operating temperature range | -18 - 49 °C |
| Sound pressure level (Lpa) | 66,3 dB |
| Sound power level (Lwa) | 74,2 dB |
| Vibration level | 2,5 m/s ² |
| Magazine capacity | 185 pieces |
| Gauge | 22 ga. |
| Collation type 1 | Glue collated |
| Collation angle | 0 ° |

Fastener specification



Description

SFW09-C, lw stapler

Art. Nr.

4C2001N

EAN code

0741474113154