









Applications


Upholstering operations, furniture assembly, cabinets, automotive vinyl roofs and interior trim, bedding manufacture, TV and stereo grille cloth, picture frames, shoemaking, molding and roofing felt

Features & Benefits

- Heavy-duty steel cap Superior balance with minimal recoil
- One-handed magazine opening Increased productivity with less downtime
- Rear exhaust Directs oil and dust away from the work surface
- Comfort grip Reduces fatigue
- Short trigger stroke Quick and precise operation
- Long lip length Makes getting into tight spots easier

Technical specifications		
Dimension (LxWxH)	218x42x167 mm	
Net weight	1 kg	
Firing mode	Trigger fire	
Air inlet	1/4" female NPT	
Operating pressure	4,1 - 6,5 bar	
Air consumption (at 60 shots per minute)	23 l/m	
Operating temperature range	-18 - 49 °C	
Sound pressure level (Lpa)	81,9 dB	
Sound power level (Lwa)	92,1 dB	
Vibration level	1,7 m/s²	
Magazine capacity	180 pieces	
Gauge	21 ga.	
Collation type 1	Glue collated	
Collation angle	0 0	

Fastener specification



Description	Art. Nr.	EAN code
SFT10XP-AT, lw stapler long nose	6S2461N	0741474125171