

SENCO[®]MAKING HARD WORK
EASIER

Applications

Wall sheathing/siding, timber frame constructions, fencing, sub-flooring, boarding and other wooden, and assembly work

Features & Benefits


- Ergonomically magnesium housing designed with comfortable rubber grip for great working experience
- No mar pad, to protect your surface
- Multi-directional exhaust deflector, deflects air away from operator
- Restrictive trigger, for precise operating
- User friendly depth of drive adjustment
- High capacity easy to load magazine
- Quick clear jam release

Coilnailer

Technical specifications

| | |
|--|-----------------------|
| Dimension (LxWxH) | 304x300x128 mm |
| Net weight | 2,49 kg |
| Firing mode | Restrictive |
| Air inlet | 1/4" female NPT |
| Operating pressure | 4,9 - 8,3 bar |
| Air consumption (at 60 shots per minute) | 220 l/m |
| Operating temperature range | -18 - 49 °C |
| Sound pressure level (Lpa) | 91 dB |
| Sound power level (Lwa) | 104 dB |
| Vibration level | 1,5 m/s ² |
| Magazine capacity | 275 pieces |
| Collation type 1 | Wire collated |
| Collation type 2 | Plastic collated 16mm |
| Collation angle | 15 ° |

Fastener specification



Description

S65CNP, coilnailer, restrictive

Art. Nr.

8G2001N

EAN code

8715274168616