

TECHNICAL SPECIFICATION



EVOGuard®C1 Industrial Visor

EVOGuard®C1 Industrial Visor / ADA240-060-000



DESCRIPTION

EVOGuard®C high performance industrial visors provide comprehensive facial coverage without limiting movement. The optical class 1 visor range offers UV protection and a panoramic view with minimal distortion.

Fully compatible with EVOGuard® browguard systems and *EVO® helmet models, the C1 visor offers up to AT rated impact protection and is also suitable for use with the Force®8 half mask and P3 filters.

*Excluding EVO®6100 and EVO® VISTA® ranges.

OPTIONS

EVOGuard®C1 Industrial Visor (ADA240-060-000)

SAFETY STANDARDS

EN 166 • EN 170



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Manufacturer's Trademark
JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s
Maximum protection for face shields
A - When fitted to EVO® helmets



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Resistance to Molten Metals and Hot Solids (optional)
9



BSI Kitemark
Yes



Product Weight
185g



Kit
Supplied With: EVO® 2,3,5,DS, Lite, Skyworker™
Arms. EVO8/EVOLite Badgeholder Arms.
EVOGuard® Browguard Mounting System

Lens Thickness - edge
1.70mm



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B - When fitted to EVOGuard® browguard



Protection from Liquid Splash
3



Visor Length
18.5cm

Material
Polycarbonate Shield



Recyclable
Yes

Lens Thickness - centre
2.00mm

FEATURES



Compatibility

EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Impact

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.



UV Protection

Visor filters harmful UV radiation to protect the eyes whilst also offering high light transmission and enhanced colour recognition.



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement. EVOGuard® MAX visors offer enhanced coverage with an integral chinguard.



Helmet & Browguard Integration

Compatible with EVO® helmet models and EVOGuard® browguard systems. Visor supplied with dual system clips for mounting to a helmet or browguard.

RANGE

VIDEOS

www.youtube.com/watch?v=_VnTgBRRT9E



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-evoguard.pdf \(PDF\)](#)

