

# **SYSTEM FOR EVOLUTION® HELMETS**

The VisiLite<sup>™</sup> has been developed as a method of increasing worker visibility without dazzling colleagues.

VisiLite<sup>™</sup> EVOLite<sup>®</sup> AHV860-000-800 VisiLite<sup>™</sup> Multi: Fits EVO<sup>®</sup> 2/3/5 AHV855-000-800





# **VISILITE™ FEATURES**



#### Standards, Testing & Performance Mode1: Static (9hrs) Modes & Mode2: Fast flash (150hrs) Runtimes Mode3: Slow flash (190hrs) Standard Charge: Approx 4.0 hours **Charge Time** Fast Charge: Approx 2.5 hours Operating +50°C to -10°C **Temperature** 14°F and 122°F Range: **IP Rating** IP54





### 50m VISIBILITY

- Independently tested for luminous intensity, visibility in darkness & flash rate
- During optical testing Visilite™ remained visible up to a distance of 50m.



# FLEXIBLE FIBRE OPTIC

• Ultra flexible, durable clear fibre optic withstands knocks and scrapes.



# EASY SECURE FIT

- Simply clip onto the sides and rear of the safety helmet.
- Quick release for replacement or USB charging.



# **DURABLE**

- The clips and main housing are made from highly durable ABS.
- The main housing is sealed to protect against dust and dirt.



# **USB RECHARGEABLE**

- Easily rechargeable with a USB charging supply; PC, Mains or Car.
- Can be charged while fitted to the helmet.
- Micro USB cable supplied.



# **ADVERSE WEATHER**

- Visilite™ is splash proof making it suitable for use in wet weather conditions.
- It has an operating Temperature Range of: +50°C to -10°C (14°F and 122°F).







JSP LTD Worsham Mill, Minster Lovell, Oxford, OX29 0TA, England Tel: +44 (0)1993 826050 Fax: +44 (0)1993 824411 uksales@jsp.co.uk export@jsp.co.uk www.jsp.co.uk lssued: 07/16 ©Copyright JSP Ltd 2016. All Rights Reserved



