

# ASTRA

## DUAL VOLTAGE FLOODLIGHTS

The Astra Site floodlight offers a dual voltage input from 110-240V, supplied with pre-wired 1M cable and U shaped mounting bracket for fast easy installation



### Features

- IP65
- IK07
- 3 Year Warranty
- U shaped Mounting Bracket



### Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
ADVF50Y	Astra Dual Voltage Floodlight 50W 5500lm 4000K IP65 Yellow	5500lm		50W	110 lm/W

### Product Information

Warranty	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Voltage	110-240V
Material (Body/Housing)	Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 50,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C



# ASTRA

## DUAL VOLTAGE FLOODLIGHTS

### Packaging Information

Dimensions (mm)	L: 180 x W: 165 x D: 25 mm
Product Net Weight (kg)	0.72 kg
Barcode	5055807630276
Box Dimensions (mm)	L:190 x W: 40 x D: 220 mm
Box Gross Weight (kg)	0.66 kg

Units/Outer Carton	20
Outer Carton Barcode	15055807630273
Outer Carton Dimensions (mm)	L: 460 x W: 235 x D: 400 mm
Outer Carton Gross Weight (kg)	13.8 kg

