

**POWERED by**  
**HONDA™**

**BUILT FOR**  
**PROFESSIONAL USE**



## B2565HG - SPECIFICATIONS

Engine:	HONDA GX200 4-Stroke 196cc
Pump	General Interpump TP2530J34UIL
Max Pressure	2500PSI
Flow Rate	11.4 l/min
Unloader	Built-In
Frame	Powder-coated Steel

## FEATURES

LOW PRESSURE CHEMICAL INJECTOR  
POWDER COATED STEEL FRAME  
10" PNEUMATIC TYRES  
ENGINE OIL 10W 30 OR 15W 40  
PUMP OIL 30W NON DETERGENT

## ACCESSORIES INCLUDED

¼" 8m HIGH PRESSURE STEEL BRAIDED HOSE  
SPLIT WAND ASSEMBLY WITH GUN  
#035 QUICK CONNECT NOZZLES 0° 15° 40° SOAPER  
SPLIT LANCE, O-RING

## PUMP SPARES

GENERAL TP2530J34UIL  
85.139.020SB  
PUMP REBUILD KIT  
73.139.020  
REPLACEMENT UNLOADER  
RK1102



## SHIPPING

DIMENSIONS	L.635 X W.533 H.533MM
WEIGHT	42KG
UNITS PER PALLET	12

