

CD-3513HWBSGEN

389cc Honda GX390 3500 PSI

POWERED by
HONDA™

BUILT FOR
PROFESSIONAL USE



5YR
LIMITED
PUMP
WARRANTY

STAINLESS
STEEL
FRAME

THE BE COOL
DRIVE FEATURE
DRAWS COOL AIR INTO PULLEY AND
KEEPS YOUR SLOW RUNNING PUMP
25% COOLER

GX
Engine **3**
YEAR
WARRANTY

CD-3513HWBSGEN - SPECIFICATIONS

Engine:	HONDA GX390 4-Stroke 389cc
Pump	General Interpump TSS-1511
Max Pressure	3500PSI
Flow Rate	15.1 l/min
Unloader	Block Mount
Frame	Stainless Steel

FEATURES

LOW PRESSURE CHEMICAL INJECTOR
TWIN V-BELT DRIVE
SLOW RUNNING PUMP FOR LONG LIFE
STAINLESS STEEL FRAME
13" PNEUMATIC TYRES
ENGINE OIL 10W 30 OR 15W 40
PUMP OIL 30W NON DETERGENT

ACCESSORIES INCLUDED

3/8" 15m GREY NON MARKING HOSE
36" GUN/WAND/COUPLINGS
#4 QUICK CONNECT NOZZLES 0° 15° 40° SOAPER

PUMP SPARES

GENERAL TS1511
85.139.005B
REPLACEMENT UNLOADER
85.300.032



SHIPPING

DIMENSIONS	L.864 X W.711 H.686MM
WEIGHT	97KG
UNITS PER PALLET	3

