

# PE-5024HWEBGEN 688cc Honda GX690 5000 PSI



# **BUILT FOR PROFESSIONAL USE**



## PE-5024HWEBGEN - SPECIFICATIONS

Engine: Pump Max Pressure Flow Bate Unloader Frame

HONDA GX690 4-Stroke 688cc General Interpump TS1819 5000PSI 18.9 I /min Block Mount Steel

### **FEATURES**

LOW OIL ALERT ENGINE TWIN V-BELT DRIVE SLOW RUNNING PUMP FOR LONG LIFE POWDER COATED STEEL ROLL CAGE FRAME 4 X 13" PNEUMATIC TYRES 26.5 LITERS FUEL TANK INCLUDES BRAKING SYSTEM ENGINE OIL 10W 30 OR 15W 40 PUMP OIL 30W NON DETERGENT

#### ACCESSORIES INCLUDED

3/8" 15m HIGH PRESSURE STEEL DOUBLE BRAID HOSE 36" GUN WAND ASSEMBLY WITH PA VEGA GUN #5 QUICK CONNECT NOZZLES 0° 15° 40° SOAPER

PUMP SPARES GENERAL TS1819 85.139.028B





SHIPPING DIMENSIONS WFIGHT UNITS PER PALLET

#### L.1219 X W.813 H.864MM 196KG 2





www.bepressure.co.uk BE Pressure UK (Genpower Ltd) Isaac Way, Pembroke Dock, Pembrokeshire SA72 4RW Tel: +44 (0) 1646 687 880 Email: sales@genpower.co.uk