

# X-3513HWBGENCD

389cc Honda GX390 3500 PSI

**POWERED by**  
**HONDA™**

**BUILT FOR**  
**PROFESSIONAL USE**



**5YR**  
LIMITED  
PUMP  
WARRANTY

**THE BE COOL**  
**DRIVE FEATURE**  
DRAWS COOL AIR INTO PULLEY AND  
KEEPS YOUR SLOW RUNNING PUMP  
**25% COOLER**

**GX** Engine **3** YEAR WARRANTY

## X-3513HWBGENCD - SPECIFICATIONS

Engine:	HONDA GX390 4-Stroke 389cc
Pump	General Interpump TSS-1511
Max Pressure	3500PSI
Flow Rate	15.1 l/min
Unloader	Pump Mount
Frame	Steel

## FEATURES

LOW PRESSURE Q/C CHEMICAL INJECTOR  
TWIN V-BELT DRIVE  
SLOW RUNNING PUMP FOR LONG LIFE  
EXTERNAL MOUNT UNLOADED  
13" PNEUMATIC TYRES  
ENGINE OIL 10W 30 OR 15W 40  
PUMP OIL 30W NON DETERGENT  
REPLACEMENT BELT

## ACCESSORIES INCLUDED

3/8" 15m GREY NON MARKING HOSE  
36" GUN WAND, COUPLINGS  
#4 QUICK CONNECT NOZZLES 0° 15° 40° SOAPER

## PUMP SPARES

GENERAL TS-1511  
85.139.005AB  
UNLOADER REPAIR KIT  
85.300.037

## INTERPUMP



## SHIPPING

DIMENSIONS	L.864 X W.711 H.660MM
WEIGHT	96KG
UNITS PER PALLET	3

