

Wide Rib Rubber

Wide Rib Rubber is a low cost, surface covering suitable for use in a wide variety of applications. The wide ribbed surface provides excellent grip for both floor surfaces and work areas alike. It is easy to cut and can be laid loose or glued/fixed down for a more permanent solution. Available in two different thicknesses, 3mm and 6mm, Wide Rib Rubber is suitable for medium to heavy duty use.

Features

- Typical applications: Low-cost surface covering, suitable for industrial flooring, aisles, work benches, vehicle interiors, kennels, livery enclosures and animal grooming areas.
- Material: 100% Rubber.
- Cleaning: Wash with cold water, use vacuum cleaner, or use pressure pump to remove dirt. The use of hard detergents is not recommended.
- Sustainability: REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- Warranty: Lifetime.



Black only



















For our icon glossary please visit: bluediamond.uk.com/glossary For more information about this product or, to place an order click here

| Code | Metric | Imperial | Thickness | Weight | Туре | Colour |
|---------|-------------|----------|-----------|---------|--------------------|--------|
| WR391 | 90cm x 10m | 3' x 33' | 3mm | 33.75kg | Roll | Black |
| WR691 | 90cm x 10m | 3' x 33' | 6mm | 74.25kg | Roll | Black |
| WR3122 | 120cm x 10m | 4' × 33' | 3mm | 45kg | Roll | Black |
| WR6122 | 120cm x 10m | 4' × 33' | 6mm | 99kg | Roll | Black |
| WR391C | 90cm wide | 3' wide | 3mm | 3.38kg | Cut length - per m | Black |
| WR691C | 90cm wide | 3' wide | 6mm | 7.43kg | Cut length - per m | Black |
| WR3122C | 120cm wide | 4' wide | 3mm | 4.5kg | Cut length - per m | Black |
| WR6122C | 120cm wide | 4' wide | 6mm | 9.9kg | Cut length - per m | Black |

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number Please note, the thickness can be +/- 0.3 to 0.5mm. Roll tolarance - width and length +/- 2%



Wide Rib Rubber

| Technical Specification | | | | |
|--------------------------------|---|--|--|--|
| Slip resistant: | Great slip resistance to level 2 | | | |
| Anti-fatigue: | Good anti-fatigue properties, resistant to level 1 | | | |
| Wear resistant: | Great wear resistance to level 2, suitable for medium to high footfall | | | |
| Cut to length: | Yes, mat can be cut to length | | | |
| Cut to size: | Yes, mat can be cut to bespoke sizes | | | |
| Disability friendly: | ability friendly: Yes, the low profile makes it suitable for wheelchair users | | | |
| Dry area: | Yes | | | |
| Wheeled area: | area: Yes, the low profile allows easy access for lightweight wheeled traffic | | | |
| Impact resistant: | Yes | | | |
| Product testing: | Hardness Shore A ±5 70° - ISO 7619-1 SG (g/cm²) 1.5 - ISO 2781 Tensile (N/mm²) 3.5 - ISO 37 Elongation % 300 - ISO 37 Compression % 43 - ISO 37 Tear Strength 12 - ISO 34-1 Abrasion mm³ 480 - ISO 37 | | | |
| Sustainability: | REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) Contributes to a cleaner environment by reducing the need to use cleaning chemicals | | | |
| Temperature resistance: | -20C° to +70C° | | | |
| Cleaning: | Wash with cold water, use vacuum cleaner or, use a pressure pump to remove dirt. The use of hard detergents is not recommended | | | |