

Jetstream® Constructor Kits

Jetstream®TH2P R SL Constructor Kit / CBP020-000-000



DESCRIPTION

Jetstream® is a belt-mounted rechargeable respirator with a large capacity disposable filter supplying filtered air through a highly flexible reinforced hose to a variety of head tops for different applications.

The Jetstream® Constructor kit carry case contains:

 $\ensuremath{\mathsf{EVO}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathbb{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\space{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\mathsf{\$}}\xspace{\ensuremath{\space{\spac$

TH2P R SL dust or TH2A2P R SL gas and dust filters Flow meter Rechargeable battery

Multi-region plug adaptor

OPTIONS

Jetstream®TH2P R SL Constructor Kit (CBP020-000-000)

Jetstream® TH2A2P R SL Constructor Kit (CDP020-000-000)

SAFETY STANDARDS

EN 397 • EN 166 • EN 12941



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS



Impact Resistance 50 Joules

Maximum Temperature +50°C

HDPE Shell



Yes Textile



Ventilation

Harness



No



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use) 1



Protection from Liquid Droplets 3



BSI Kitemark Yes

Classification TH2 (Turbo Hood)

Minimum Filtration Efficiency 98%

Nominal Protection Factor 50

Face Seal Type Hypoallergenic Material

Mask Design A Turbo Hood Powered Air Purifiying Respirator (Loose Fitting)





Product Weight Head Top 884g



Filter Type P (Protects Against Solid and Liquid Aerosols)



Product Weight Power Pack & Filter 1066g



Product Weight TH2P R SL Filter 124g

FEATURES



Comfort

Waist mounted blower unit with fully automatic alarm and integrated battery attached to a wide comfortable waist belt.



Adaptable

A wide range of kits, filters and head tops are available to suit a variety of tasks.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





Resistance to Molten Metals and Hot Solids (optional) Yes - Helmet Only



Minimum Temperature -20°C



Slip Ratchet Slip



Manufacturer's Trademark JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. В



Resistance to Molten Metals and Hot Solids (optional) 9



JSPCheck Yes

Usage R (Reusable)

Maximum Total Inward Leakage (TIL) 2% When Fitted To Jetstream

UK Assigned Protection Factor 20



Exhalation Valve Yes

Latex free No

Battery Type 8 Hour Rechargable Nickel Metal Hydride (NiMH)

Noise Level 65dB

*** Gas Filters Not Compatible ***



No Face Fit Testing

As a loose-fitting respirator, Jetstream® is suitable for users with neatly trimmed, well-groomed facial hair and does not require face fit testing.



Comfort

Waist mounted blower unit with fully automatic alarm and integrated battery attached to a wide comfortable waist belt. Complete unit and belt weigh just 765g.



Simple Maintenance

Key components are available as spare parts, enabling simple maintenance and the option to purchase several head tops or filters.

RANGE

Jetstream







High Performance

180 litres of air per minute are delivered through the Jetstream® filter via a highly flexible hose to the desired head top.

Easy Cleaning

Quick and easy cleaning; hood, filter housing, blower unit, and hose can be wiped clean with a damp cloth soaked in mild detergent solution.

High Performance Filters

TH2P R SL (A Reusable Solid & Liquid, Particulate Aerosol Filter)

DOWNLOADS

Image Pack (ZIP)

doc-jetstream-constructor-kit.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.