

JETSTREAM® SPARES

PRODUCT CODE: CBU620-000-000

SPARE GAS AND VAPOUR GV-X A2PSL FILTER

TECHNICAL
SPECIFICATION

RESPIRATORY PROTECTION

INSTRUCTIONS FOR USE

Line up all fins on with the corresponding holes in the power unit and push in. Rotate anti-clockwise until all fins click to the closed position

The airflow of the power unit should be checked prior to use

Care must be taken to ensure that the correct respiratory protection device is selected for the work to be carried out. If in doubt seek professional advice

LIMITATIONS OF USE

Protection will only be offered if the Jetstream® unit is fitted correctly

This product is a respiratory protection device and should only be used as part of the JSP Jetstream system

Check airflow of the power unit before use. The power unit should operate without the low flow/battery warning buzzer sounding

If warning buzzer sounds, re-charge the battery and replace the filter (where required)

The power units for Dust and Gas/vapour are not interchangeable, Force fitting of filters will damage the unit

The use by date of the filter is printed on the outside

The working life of the filter depends on many factors including work rate, airflow and concentration of any contaminant in the atmosphere. The filter should be changed immediately if,
a.) Breathing difficulties due to clogging are experienced,
b.) Breakthrough of a contaminant is detected, or
c.) The filter becomes damaged

Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres

To obtain maximum workable life from the unit, allow the battery to run down fully before recharging

CLEANING & MAINTENANCE

Wipe with damp cloth soaked in mild detergent solution, being careful not to get liquid in the filter

Do not immerse the unit in water. Do not use abrasive substances or solvents

Cleaning the filter does not extend its life

Store the unit in an airtight container, out of direct sunlight away from chemicals, abrasive substances and in a dry atmosphere



MATERIALS

Filter Outer: ABS

Filter Media: Man made

Filter Mesh: Polythene

PERFORMANCE

Waist Mounted Unit: Blower unit with fully automatic alarm and integrated battery providing 180 LT/min of filtered air

Offers an assigned protection factor (APF) of 20 x Workplace Exposure Limit (WEL) for very fine dusts, fibres, fumes and aqueous mists

CONFORMITY

When fitted to a Jetstream Dust Power Unit, respiratory protection provided by the filter complies with European Standard EN 12941:1999; TH2

EC Certificate Number 59716, issued by BSI Product Certification

