

MAGNESIUM BULL FLOAT KIT

TECHNICAL SPECIFICATIONS

Complete kit in carry case with bull float blade (1200mm x 203mm), magnesium worm gear bracket, and 4x magnesium extension handles (45mm x 1830mm)

BENEFITS

- Lightweight and longer lasting than aluminium
- Float blade curved and balanced to prevent digging
- Blade and worm gear bracket also available separately
- Optional larger accessory blade available
- Four part handle can be extended to 7320mm
- Supplied with carry case


HOW IT WORKS



Use immediately after screeding to smooth and level the concrete surface, pushing and pulling the blade across the slab using the swaged handles. Adjust pressure and angle as needed to flatten high spots and embed aggregate, preparing the surface for final finishing.

IMPORTANT INFORMATION:


- Rinse with water between jobs to remove any built up concrete and chemicals before they set
- Check all handle connections are secure before use



TECHNICAL DATA



Bull float kit



Larger accessory blade



Bull float blade & bracket



Worm gear bracket

SKU	DAP403	DAP409	DAP404	DAP407
Weight	11kg	4.4kg	2.9kg	1.9kg
Dimensions	Blade 1200mm x 203mm, Handle dia 45mm x L1830mm	1524mm x 203mm	1200mm x 203mm	W120mm, L255mm, H155mm
Material	Magnesium, powder coated handles	Magnesium	Magnesium	Powder coated aluminium alloy
Applications	Concrete	Concrete	Concrete	Concrete
Pallet Qty	tbc	tbc	tbc	tbc



Wear appropriate PPE & avoid skin contact with wet concrete



Do not use damaged or bent components