

## Battery Charger XGT® DC40RC

Li-ion • 40Vmax • DC40RC

Standard charger developed for charging XGT® Li-lon batteries.

Standard charger that is able to charge Makita XGT® Li-Ion batteries. Charges a battery in 30 - 85 minutes, depending on the battery's capacity. Compatible with Interchangeable adapter ADP10 (optional accessory) for charging our LXT® Li-Ion batteries.





## Technical specifications

Nominal Battery Voltage 40 V Average Charging Time 30 - 170 min 30 min Charging Time 2.0 Ah Charging Time 2.5 Ah 38 min Charging Time 4.0 Ah 67 min Charging Time 5.0 Ah 85 min Continuous Input Power 200 W Power Supply Cord 2.0 m Product Dimensions (L x W x H): 156 x 209 x 84 mm • Battery Chemistry (Ni-Cd / Ni-MH / Li-Li-ion

Voltage XGT 

✓
Product net weight 0,82 kg

## User benefits

- Large charging status indicator light (clear indication by LED in 3 colours, blue, green and red, with a raised lens)
- Selectable melody sound for full charge notification
- Optimum charging control using feedback of real-time battery data
- Also works as a wall-mounted charger
- The charging performance of each charging port is as high as that of DC40RA
- · Able to perform consecutive fast charging of batteries



Link to product - www.makitauk.com

ion)

## **Related products**



**User manual** 

**Parts drawing**