



2 Piece Combo Kit **LXT®**

DLX2537ST

18V

Includes: DHP490 Combi Drill and DTD153 Impact Driver, 2 x 5.0Ah LXT Li-lon batteries, DC18SD charger and carry case

Models in kit









18V Combi Drill Brushless LXT®

DHP490

Model DHP490 is a Combi Drill powered by an 18V LXT Lilon battery.

This model ensures sufficient torque by adopting a Brushless Motor is lightweight and compact, easy to handle even in narrow spaces. Features and Benefits: Max.torque of 65Nm, Mechanical 2 speed, Electric brake, Variable speed control by trigger





Technical specifications

Nominal Battery Voltage 18 V Voltage LXT Battery Chemistry (Ni-Cd / Ni-MH / Li-Li-ion **Brushless Motor** No load speed 0 - 500 / 1900 min⁻¹ 50 / 27 Nm Max. fastening torque Hard/Soft 65 Nm Max Torque Torque setting 20 Impacts per Minute (IPM) 0 - 7500 / 28500 min⁻¹ Max. Drilling Diameter in Wood 38 mm

13 mm

13 mm

38 mm

38 mm

51 mm

User benefits

- Keyless chuck for easy bit installation and removal
- Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- Built-in LED light with pre-glow and afterglow functions illuminates the work area
- Variable speed trigger allows operator to adjust speed based on materials or application
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - www.makitauk.com

Max. Drilling Diameter in Masonry

Drilling Capacity Wood (Auger Bit)

Drilling Capacity Wood (Self-feed bit)

Max. Drilling Diameter in Steel

Drilling Capacity Flat bit Drilling Capacity Hole Saw





Impact Driver LXT® DTD153

18V • 1/4" • 170 Nm • 0 – 3 400 min⁻¹

Extra-compact brushless impact driver for quick driving

A compact and light brushless impact driver with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 170 Nm, suitable for quick driving. A handy LED light for added lighting.





Technical specifications

Nominal Battery Voltage 18 V Voltage LXT Battery Chemistry (Ni-Cd / Ni-MH / Li-Li-ion **Brushless Motor** No load speed 0 - 3400 min⁻¹ Max Fastening Torque Impact Drill 170 Nm Impacts per Minute (IPM) 0 - 3600 min⁻¹ Tightening Capacity Standard Bolt M5 - M16 1/4 " **Driving Shank** Sound Power Level (L_{WA})

107 dB(A)

Sound Pressure Level (L_{pA}) 96 dB(A)

Noise Uncertainty (K Factor) 3 dB(A) Vibration Level, Impact Tightening of 13,0 m/s² Fasteners of the Maximum Capacity of

User benefits

- Low power consumption thanks to brushless motor
- The rubber coating on the handle ensures a firm working grip
- The screw tip is securely held in place by a quick lateral stroke
- LED light illuminates the work site
- Quick mount for 1/4 "screwdriver
- Battery protection system automatically shuts off power when the battery level is low
- Variable speed control dial enables user to match the speed to the application for greater versatility



Link to product - www.makitauk.com

the Tool

Related products kit

Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18SDBattery Charger LXT®





194250-8

Adaptor Chuck - 1/4 Hex Keyless



821550-0

Makpac case (2)



837670-0

MakPac (2) Inlay



Other - DHP490

User manual

Parts drawing



Other - DTD153

User manual

Parts drawing