



2 Piece Combo Kit LXT

DLX2549TJ

18V

Includes: DHP492 Combi Drill and DTD173 Impact Driver



Models in kit



Combi Drill LXT®
DHP492



Impact Driver LXT®
DTD173

Combi Drill LXT®

DHP492

18V

A powerful, brushless general-use impact drill for screwdriving and drilling

An efficient, brushless drill for screwdriving and drilling. A powerful max. torque of 141Nm. The main feature and benefits are: Redesigned speed change mechanism to avoid gear disengagement, Controller protection has been revised to enhance the protection for electronic components during variable speed control by the trigger.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Brushless Motor	✓
No load speed	0 - 550 / 2100 min ⁻¹
Max. fastening torque Hard/Soft	130 / 65 Nm
Max Torque	141 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 8250 / 31500 min ⁻¹
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Wood (Auger Bit)	50 mm
Drilling Capacity Wood (Self-feed bit)	76 mm
Drilling Capacity Flat bit	40 mm
Drilling Capacity Hole Saw	152 mm
Driving Shank	1/2"-20UNF "

User benefits

- Highly efficient and compact machine for professional use
- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low
- Electronic overload protection protects the user and the device
- Keyless chuck for easy bit installation and removal
- Compact and lightweight for reduced operator fatigue
- Electric brake for maximum productivity and increased operator safety

Link to product - www.makitauk.com



Impact Driver LXT®

DTD173

18V, 1/4", 180 Nm, 0 - 3 600 min⁻¹



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Brushless Motor	✓
No load speed	0 - 1100 / 2100 / 3200 / 3600 min ⁻¹
Max Fastening Torque Impact Drill	20 / 50 / 170 / 180 Nm
Impacts per Minute (IPM)	0 - 1100 / 2600 / 3600 / 3800 min ⁻¹
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Driving Shank	1/4 "
Sound Power Level (L _{WA})	108 dB(A)
Sound Pressure Level (L _{pA})	97 dB(A)

User benefits

- Electronic 4 stage impact power selection for added versatility
- Well balanced with a low center of gravity for easy operation
- Slim body design for a good grip
- Electric brake for maximum productivity and increased operator safety
- Anti wobbling bit structure

Link to product - www.makita.com



Related products kit

Standard AC

821551-8

Makpac case (3)



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

122576-8

Stopper Pole



122D10-2

Grip Assembly



821550-0

Makpac case (2)



837916-4

MakPac (2) Inlay



Other - DHP492

User manual

Parts drawing

Other - DTD173

User manual

Parts drawing