



Performance. Power.  
Productivity.™

# DS5525-18V

## 55 mm 18v Li-ion 2500 RPM Auto-feed Screwdriver

Battery powered high torque motor is a great fit for general contractors that need the versatility to do a wide variety of jobs. Added torque provides plenty of power for hard woods, cement board, and subfloor. Lower speed is ideal for applications where drill point screws are used to cut through heavy steel.



### Specifications

Item #: . . . . . 7X2001N (EU-version)  
 . . . . . 7X7001N (UK-version)  
 RPM: . . . . . 0-2,500  
 Torque: . . . . . 90 inlb  
 Voltage: . . . . . 18  
 Weight: . . . . . 2.24 kg  
 Height: . . . . . 241 mm  
 Length: . . . . . 381 mm  
 Width: . . . . . 86 mm  
 Drives per charge: . . . 500-700

### Fastener Specifications

Screw Lengths: . . . . . 25 mm – 55 mm  
 Screw Diameters: . . . 3,5 mm– 4,8 mm  
 Drive Type: . . . . . Phillips & Square drive



### Applications

For drywall (to wood or steel studs), subfloor, cement board, underlayment, sheathing to steel, metal framing, structural steel decking, rigid foam insulation.

### Features and Benefits

- 18v Li-ion technology (Includes 2 batteries)
- 2500 RPM high torque motor
- Patent pending corner-fit feed system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change
- Variable speed trigger with lock and reverse
- Belt hook -right or left handed adjustable
- Comes complete with two drive bits, drywall and wood nosepiece, two 18v Li-ion batteries, charger, and Blow Molded Case



**SENCO**<sup>®</sup>Performance. Power.  
Productivity.<sup>™</sup>**DS5525-18V**

## Features

**Tool Free Adjustable Nose Piece**

With easy-to-read length markings, adjusts to screw lengths of 25 mm - 55 mm

**Super Hard Drive Bits**

The longest-lasting drive bits available

**Patent-Pending Corner-Fit Feed System**

With better line of sight. Smooth operation and excellent wall/corner access.

**Adjustable Depth-of-Drive with Depth Lock**

For flush drive or countersink

**Reverse Switch**

To back out driven screws

**Variable Speed Trigger**

Allows user to regulate RPMs for self-tapping screws into steel and other applications

**Wood Nose Piece**

Insures a straight drive in harder materials

**Drywall Nose Piece**

Dimples drywall just right

**Quick Slide bit release**

Move the slide and the bit easily drops in or out

**0-2500 RPM High Torque Motor**

Specially designed to torque screws in without bogging down

**Second Hand Grip**

Helps combat worker fatigue

**Trigger Lock****Comfortable Grip**

Ergonomically designed for extra comfort and better productivity with less exertion

**Belt Hook**

Keep the tool within reach for improved productivity

**Powerful 18-volt Li-ion battery with Fuel Gauge (2 batteries)**

Provides optimum balance of power, weight and run-time across the full range of screws, 60 minute charger

**Includes Blow Molded Case**Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on auto-feed screw systems and how SENCO will save you time, reduce costs and increase quality, visit our website at: [www.senco-emea.com](http://www.senco-emea.com)