

TECHNICAL SPECIFICATION



10m Rope & Grab

10m Rope & Grab / FAR0810



DESCRIPTION

Fall Arrest system with 12mm diameter kernmantle rope anchorage line and non-openable stainless steel rope grab equipped with energy absorber. The anchorage line has one connector, with the other end folded back and stitched 10cm.

OPTIONS

10m Rope & Grab (FAR0810)

SAFETY STANDARDS

EN 353-2



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Fall Indicator
No

Length
10m

Material
12mm Kernmantle Rope

Shock Absorber
External

Rope Ends
1 Side 1 Connector and. Other Side Folded Back and Stitched 10cm.

Protective Rope Sleeve
No

Adjustment Device
Non-Openable Stainless Steel Rope Grab



Product Weight
2110g

Delivered With
2 Screwgate Connectors In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0810-far0811-far0812.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

