









## PCX 12/36 & 13/40 PLATE COMPACTORS





## **FEATURES & BENEFITS**

- Foldable mounted guide handle offers superior manoeuvrability and can be lowered to operate under obstacles and close to form work.
- Reinforced centrifugal clutch ensures longer belt life, and simplified belt adjustment.
- Lifting points and front lift cage offer easier loading and unloading for operator convenience.
- Large 9.5 litre water tank is built into the protective frame.
- Choice of Honda or Loncin petrol engines.
- Angled holes on spray bar allow complete water coverage over the full width preventing any asphalt pick-up on plate bottom.
- The spraybar is fully protected from damage, easily positioned, with integral paving pad clamp points.
- Life lubricated vibration bearings.



WATER SPRAY KIT OPTION AVAILABLE



WHEEL KIT OPTION AVAILABLE

## **TECHNICAL SPECIFICATIONS**

Model
Plate Width
Plate Length
Centrifugal Force
Travel Speed
Vibration level
Noise Level

Model PCX 12/36 Part No. Engine Power

Weight
Static Pressure

**Options** 

OPP/65/DIO

OPP/66/DIO

OPP/74/DIO

OPP/70S/DIO

OPP/71S/DIO

PCX 12/36

(mm) 360 (mm) 720 (kN) 12 (m/min) 20 (m/sec²) 4.74 (dB(A) 105

Honda GX120

PCX 12/36 Block Paving Pad

PCX 13/40 Block Paving Pad

PCX 12/36 Water Spray Kit

PCX 13/40 Water Spray Kit

PCX 12/36 & 13/40 Wheel Kit

FC3600E (Hp / kW) 4.0 / 3.0 (kg) 81 (kg/m²) 586 Model

Plate Width
Plate Length
Centrifugal Force
Travel Speed
Vibration level
Noise Level

Model PCX 13/40

Part No. Engine Power Weight Static Pressure

Model PCX 13/40

Part No. Engine Power Weight Static Pressure

Model PCX 13/40

Part No. Engine Power Weight Static Pressure PCX 13/40

(mm) 400 (mm) 606 (kN) 13 (m/min) 20 (m/sec²) 3.20 (dB(A) 105

Honda GX120

FC4000E (Hp / kW) 4.0 / 3.0 (kg) 83.5 (kg/m²) 520

Honda GX160

FC4020E (Hp / kW) 5.5 / 4.0 (kg) 85.5 (kg/m²) 518

Loncin H135

FC4060E (Hp / kW) 3.5 / 2.6 (kg) 83.5 (kg/m²) 520



