

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Screwing and drilling

AID 14,4/3,0 1/4 inch

Order no. 379.522



Technical attributes	AID 14,4/3,0 1/4 inch
Battery voltage	14,4 V
Battery capacity	3,0 Ah
Max. torque	145 Nm
No load speed	0-2400 rpm
Tool fixture	1/4"
Weight with battery	1,4 kg

Standard equipment
2 batteries AP-K 14,4/3,0
1 rapid charger CA-K 14,4/60
1 carry case

Cordless impact driver 14,4 V with lithium-ion technology

- Clockwise and counterclockwise rotation; middle setting: safety lock
- Charge indicator
- Rapid battery charger (charge time 60 min)
- Integrated LED light
- Tool holder for 1/4" bit tools
- Ergonomic design
- Ergonomically designed, non-slip, soft grip handle for safe, comfortable working

Accessories

Rapid charger



Charging time 60 mins. for Li-Ion battery 14,4 V.

QTY/PKG: Order no.**1 348.694**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Screwing and drilling

Battery pack



Battery pack Li-Ion 14,4 V / 3,0 Ah for AID 14,4 and AD/ADH 14,4.

QTY/PKG: Order no.**1 391.018**

Belt clip for AID, AD/ADH 14,4

**QTY/PKG: Order no.****1 395.722**

Bit



Design PH size 2, C 6,3.

Dimensions QTY/PKG: Order no.
in mm:**25 5 395.927**

Design PH size 2, E 6,3. Can be used with screw magazine attachment M-DW.

Dimensions QTY/PKG: Order no.
in mm:**175 2 395.900**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Screwing and drilling

Bit holder



Magnetic, design PH size 2, E 6,3.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

50	1	395.919
----	---	---------