

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Surface finishing sanding, random orbital

### ORE 150-5 Set

Order no. 379.611



Technical attributes	ORE 150-5 Set
Power input	350 watt
No load speed	5800 - 10000 rpm
Orbit rate, no load	11600 - 20000 opm
Orbit	5,0 mm
Backing pad	Ø 150 mm
Dust extraction connection	Ø 27 mm
Weight	2,1 kg

#### Random-orbit sander with speed control in set

- Sanding speed to suit the material due to speed control. No more damaged workpieces.
- Effective dust extraction thanks to integrated extractor for dust-free working with filter cartridge
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter and guarantees maximum service life
- PES filter cartridge with cyclone function for dust-free and efficient working
- Light-weight single-hand power tool with the best ergonomics and special balancing system for low-vibration operation. Provides comfortable and joint-friendly working conditions
- Possible to connect external dust extraction
- High-performance sanding pad: highly durable and abrasion-resistant
- Velcro pad and sanding discs with 15-hole design (8 outside, 6 inside, 1 in the centre) for optimum low-dust extraction
- Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- Suitable for coarse and intermediate sanding of surfaces, flat areas, curves, shapes, final sanding of fillers
- Especially suitable for overhead work

Standard equipment	
1 velcro sanding pad hard	
1 PES microfilter cartridge with filter	
Sanding tool starter set: 3x PURFLEX, 3x SELECTFLEX (various grit sizes)	
1 hexagon socket wrench, SW 5	
1 carrying case L-BOXX 238 414.093	
1 case insert	407.895