

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Mixers

MXE 1302 + WR3R 140

Order no. 388.122



1260 watt 2-gear mixer with speed control

- Large, rugged 2-gear unit with optimum ratios for powerful torque and correct speed for different materials
- FR full-wave electronic control: with soft start, temperature monitoring, overload protection

| Technical attributes | MXE 1302 + WR3R 140 |
|-----------------------------|---------------------|
| No load speed 1st gear | 150-530 rpm |
| No load speed 2nd gear | 200-750 rpm |
| Power input | 1260 watt |
| Power output | 690 watt |
| Tool fixture | M 14 |
| Clamping neck Ø | 43 mm |
| Max. mixing paddle Ø | 160 mm |
| Size (W x L x H) | 370 x 235 x 315 mm |
| Weight (with mixing paddle) | 5,5 kg |

Standard equipment

1 helix paddle WR3R
140x600 M14

1 open-ended wrench SW
19

1 open-ended wrench SW
22

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Mixers

and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges

- The required final rotation speed can be set via the thumb wheel on the protective cap and preselected for the mixing operation
- Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation. With anti-slip coating
- Four corner guards with rubber buffer and inserted metal plate provide secure storage during transportation and offer protection against shocks and impacts at the building site
- Protective cap above the motor housing guides the cooling air flow and prevents the ingress of rain water
- The flexible rubber grommet over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- With 4 metres H07-RNF cable
- With mixing paddle WR3R for mixture: tough to heavy. Mortar, plaster, screed, concrete, ...