

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Measuring technology/Laser

ALC 2/1

Order no. 393.665



Technical attributes	ALC 2/1
Number of lines	1 horizontal/1 vertical
Visible area lines	180° horizontal/vertical
Precision	± 0,3 mm/m
Self-levelling range	± 6 °
Max. working range	30 m
Max. range with receiver	60 m
Operation duration	25 h
Temperature range	-18° - +50 °C
Laser class	2
Weight	0,28 kg

Self-levelling crossline laser

- Two 180° visible laser lines which can be switched individually
- Cross-laser projection
- Self-levelling
- Optical warning signal when self-levelling range exceeded
- Self-levelling which can be switched off
- Highly visible laser beam thanks to anti-reflective glass
- Simple On-button operation
- Connectable pulse function for use with receiver
- 1/4" thread for tripod

Standard equipment

Batteries 3x AA

1 wall holder magnetic
WB-M 1/4-ALC

1 belt pouch BEP ALC 2/1

1 carry case

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Measuring technology/Laser

Accessories

Laser target plate



Amplifies the projection of the red laser beam over long distances or in a bright environment. Magnetic and can be set up.

QTY/PKG:	Order no.
----------	-----------

1	393.606
---	---------

Wall and ceiling mount



Adjustable wall and ceiling holder with additional clamping function. 1/4" device connection.

QTY/PKG:	Order no.
----------	-----------

1	393.614
---	---------

Belt pouch



Belt pouch for ALC 2/1.

QTY/PKG:	Order no.
----------	-----------

1	393.622
---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Measuring technology/Laser

Laser wall holder



Magnetic 90° wall holder made of aluminium with 1/4" device connection.

QTY/PKG: **Order no.**

1 393.630

Carry case



Suitable for laser ALC 2-F with additional compartment for ALC 2-1.

QTY/PKG: **Order no.**

1 393.657



Suitable for laser ALC 2/1 and receiver with holder.

QTY/PKG: **Order no.**

1 393.908

Case insert

Suitable insert for carry case L-BOXX® 238 for the three laser with laser receiver and accessories.

QTY/PKG: **Order no.**

1 399.264

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Measuring technology/Laser

Carrying case L-BOXX®



The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXX®es optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

External dimensions x W x H:	Internal dimensions x W x H:	Weight:	QTY/PKG:	Order no.
442 x 357 x 253	378 x 306 x 209	2,8	1	414.093

Insert for carrying case L-BOXX®



Soft insert mat made of rubber suitable for the L-BOXX® type 238. Protects the Boxx and the material on the floor from damage during transportation.

QTY/PKG:	Order no.
1	419.389

Trolley L-BOXX®



Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.

Dimensions in mm:	Weight:	QTY/PKG:	Order no.
646 x 492 x 182	3,8	1	419.400