

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### ALC 2-F

**Order no. 393.673****Floor layer laser**

- Two visible laser lines at 90° angle in front of and behind the device
- Highly visible laser beam thanks to anti-reflective glass
- Robust aluminium housing with integrated stop rail and three steel ball device feet

Technical attributes	ALC 2-F
Number of lines	2 at 90° angle
Visible area lines	90° angle
Precision	± 0,3 mm/ m
Max. working range	20 m
Operation duration	10 h
Temperature range	-10° - +50 °C
Laser class	2
Weight	1,09 kg

**Standard equipment**

2 target plates red FTR-M

Batteries 3x AA

1 carry case

**Accessories****Laser target plate**

Amplifies the projection of the red laser beam over long distances or in a bright environment. Magnetic and can be set up.

**QTY/PKG:    Order no.****1                    393.606****Carry case**

Suitable for laser ALC 2-F with additional compartment for ALC 2-1.

**QTY/PKG:    Order no.****1                    393.657**

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### Case insert

Suitable insert for carry case L-BOXX® 238 for the three laser with laser receiver and accessories.

QTY/PKG:	Order no.
----------	-----------

1	399.264
---	---------

### Carrying case L-BOXX®



The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXX®es optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

External dimensions L x W x H:	Internal dimensions L x W x H:	Weight:	QTY/PKG:	Order no.
442 x 357 x 253	378 x 306 x 209	2,8	1	414.093

### Insert for carrying case L-BOXX®



Soft insert mat made of rubber suitable for the L-BOXX® type 238. Protects the Boxx and the material on the floor from damage during transportation.

QTY/PKG:	Order no.
----------	-----------

1	419.389
---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### Trolley L-BOXX®

---



Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.

Dimensions in mm:	Weight:	QTY/PKG:	Order no.
----------------------	---------	----------	-----------

---

646 x 492 x 182	3,8	1	419.400
--------------------	-----	---	---------