

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### ALC 1-360

Order no. 393.681



Technical attributes	ALC 1-360
Number of lines	1 horizontal
Visible area lines	360° horizontal
Precision	± 0,1 mm/m
Self-levelling range	± 8 °
Max. working range	30 m
Max. range with receiver	60 m
Operation duration	35 h
Temperature range	-18° - +50 °C
Laser class	2
Weight	0,45 kg

#### 360° line laser for highest demands

- A visible 360° laser line
- Self-levelling
- Optical warning signal when self-levelling range exceeded
- Highly visible laser beam thanks to anti-reflective glass
- Simple On-button operation
- Connectable pulse function for use with receiver
- 1/4" thread for tripod

#### Standard equipment

Batteries 3x D

1 wall/ceiling holder WBC  
1/4-ALC

1 carry case

#### Accessories

##### Laser target plate



Amplifies the projection of the red laser beam over long distances or in a bright environment. Magnetic and can be set up.

**QTY/PKG:**    **Order no.****1**                    **393.606**

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### Wall and ceiling mount

---



Adjustable wall and ceiling holder with additional clamping function.  
1/4" device connection.

QTY/PKG:	Order no.
----------	-----------

---

1	393.614
---	---------

### Laser wall holder

---



Magnetic 90° wall holder made of aluminium with 1/4" device connection.

QTY/PKG:	Order no.
----------	-----------

---

1	393.630
---	---------

### Carry case

---



Suitable for laser ALC 1/-360 and receiver with holder.

QTY/PKG:	Order no.
----------	-----------

---

1	393.649
---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### Case insert

Suitable insert for carry case L-BOXX® 238 for the three laser with laser receiver and accessories.

QTY/PKG:	Order no.
----------	-----------

1	399.264
---	---------

### Carrying case L-BOXX®



The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXX®es optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

External dimensions L x W x H:	Internal dimensions L x W x H:	Weight:	QTY/PKG:	Order no.
442 x 357 x 253	378 x 306 x 209	2,8	1	414.093

### Insert for carrying case L-BOXX®



Soft insert mat made of rubber suitable for the L-BOXX® type 238. Protects the Boxx and the material on the floor from damage during transportation.

QTY/PKG:	Order no.
----------	-----------

1	419.389
---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### Trolley L-BOXX®

---



Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.

Dimensions	Weight:	QTY/PKG:	Order no.
in mm:			

---

646 x 492 x	3,8	1	419.400
182			