

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Measuring technology/Laser

LR 1

Order no. 393.703



Laser receiver

- Receiver for horizontally and vertically pulsed laser lines. Can be used with ALC 1-360 and 2/1
- Adjustable display precision
- Display on front and back
- Acoustic signal which can be switched off when laser received
- Floor level mark (on-Grade)

Technical attributes	LR 1
Number of lines	2 at 90° angle
Working range	30 - 75 m
Precision	I=0,75 mm / II=1,75 mm
Operation duration	30 h
Temperature range	-20° - +60 °C
Weight	0,14 kg

Standard equipment

Batteries 9V-unit

1 holder SC LR 1

Accessories

Laser receiver holder



For attachment of the laser receiver with 2 clamping jaws for fixing on levelling rules.

QTY/PKG: **Order no.**

1 394.017

Case insert

Suitable insert for carry case L-BOXX® 238 for the three laser with laser receiver and accessories.

QTY/PKG: **Order no.**

1 399.264

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Measuring technology/Laser

Carrying case L-BOXX®



The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXX®es optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

External dimensions x W x H:	Internal dimensions x W x H:	Weight:	QTY/PKG:	Order no.
442 x 357 x 253	378 x 306 x 209	2,8	1	414.093

Insert for carrying case L-BOXX®



Soft insert mat made of rubber suitable for the L-BOXX® type 238. Protects the Boxx and the material on the floor from damage during transportation.

QTY/PKG:	Order no.
1	419.389

Trolley L-BOXX®



Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.

Dimensions in mm:	Weight:	QTY/PKG:	Order no.
646 x 492 x 182	3,8	1	419.400