

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

LD 15-10 125, Kit Turbo-Jet

Order no. 405.914



Compact renovation grinder for dust-free grinding, 125 mm

- Electronic control: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- Dust extraction: prevents dust nuisance, reduces disc wear, keeps the concrete pores open for the new coating
- Reliable 1450 watt high-performance motor with sufficient power reserves
- Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and flying stones
- Extraction hood: with stepless height adjustment
- With steplessly adjustable, vibration-proof, ergonomic auxiliary handle, for optimum handling and machine control
- For fixed hose connection. Adapter with FLEX Clip connection for Ø 32 mm snap connection included in the standard equipment.
- Recessed spindle lock, to avoid unintentional activation
- Ideally suited for processing walls, ceilings and floors. Efficient and economic working thanks to optimum coordination between machine and sanding disc
- Turbo-Jet grinding disc with optimum removal rate. The wide range of diamond segments provides a considerably quieter operating performance and a more attractive sanding pattern. Ideal for surface grinding on mineral substrates.

Technical attributes	LD 15-10 125, Kit Turbo-Jet
Disc Ø	125 mm
No load speed	10000 rpm
Power input	1450 watt
Power output	950 watt
Vibration	< 6,4 m/s ²
Tool fixture	M 14
Weight	3,2 kg

Standard equipment	
1 Turbo-Jet grinding disc	348.899
1 extraction hood with rubber extraction ring	
1 handle	
3 cable clips	
1 hexagon socket wrench, SW 4	
1 extraction adapter SAD-C D25-32 AS	320.188
1 pin wrench	
1 carrying case L-BOXX® 238	414.093
1 case insert	

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Accessories

PCD grinding disc



Grinding disc fitted with polycrystalline diamond segments. For the removal of thermally sensitive coatings such as adhesives, sealants, plastic coatings, bitumen coatings from mineral substrates. The PCD segments enable coatings to be removed quickly and effectively without sticking.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	406.015
--------------	----------	----------------



PCD grinding disc, the new dimension for removal of thermal coatings from mineral substrates, masonry, oil-based paints and latex paints.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	359.416
--------------	----------	----------------

Thermo-Jet diamond grinding disc



Diamond grinding head suitable for grinding concrete parts, roughing old weathered concrete, hard cement plaster, removing shuttering protrusions and concrete runs, hardened epoxy resin coatings and the natural sintering on concrete components. High grinding capacity and service life from the innovative segment design. Optimal ground preparation for further coating.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	359.378
--------------	----------	----------------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Screed-Jet diamond grinding disc



Sanding wheel for abrasive materials. For removal of formwork transitions and concrete runs from freshly concreted surfaces, mineral adhesives, screeds, plaster, mortar, abrasive lime sand brick, sandstone, chamotte, asphalt.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	359.394
--------------	----------	----------------

Diamond disc Turbo-Jet



Turbo-Jet grinding disc with optimum removal rate. The wide range of diamond segments provides a considerably quieter operating performance and a more attractive sanding pattern. Ideal for surface grinding on mineral substrates.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	348.899
--------------	----------	----------------

Surface-Jet diamond grinding disc



Special sanding wheel for cosmetic treatment of concrete and removal of graffiti, as well as for removal of slight unevenness and transitions from concrete parts, soiling on concrete and hard plaster.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	359.424
--------------	----------	----------------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Adapter



Suitable for suction hoses using the FLEX clip system. Anti-static design.

QTY/PKG:	Order no.
----------	-----------

1	393.398
---	---------

Diamond grinding disc



Universal sanding wheel for sanding mineral surfaces.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

125 Ø	1	420.417
-------	---	---------

Guard with rubber extraction ring

The flexible rubber vacuum ring moves smoothly over the surface and provides optimum protection against dust and flying stones.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

125 Ø	1	421.111
-------	---	---------

Rubber extraction rings



The flexible rubber vacuum ring moves smoothly over the surface and provides optimum protection against dust and flying stones.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

125 Ø	1	257.246
-------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Carrying case L-BOXX®



The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXX®es optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

External dimensions x W x H:	Internal dimensions x W x H:	Weight:	QTY/PKG:	Order no.
442 x 357 x 253	378 x 306 x 209	2,8	1	414.093

Anti slip insert L-BOXX®



Soft insert mat made of rubber suitable for the L-BOXX® type 238. Protects the Boxx and the material on the floor from damage during transportation.

QTY/PKG:	Order no.
1	419.389

Case insert

Suitable insert for carrying case L-BOXX® 238. For the LD 15-10 125 / R.

QTY/PKG:	Order no.
1	414.131

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Trolley L-BOXX®



Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.

Dimensions	Weight:	QTY/PKG:	Order no.
------------	---------	----------	-----------

in mm:

646 x 492 x 182	3,8	1	419.400
--------------------	-----	---	---------