

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

LD 18-7 125 R, Kit Turbo-Jet

Order no. 408.603



1800 watt powerful grinding machine for working close to edges, 125 mm

- FV electronic control: with consistent speed control, soft start, overload protection and temperature monitoring
- Reliable 1800 watt high-performance motor with sufficient power reserves
- Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- Recessed spindle lock, to avoid unintentional activation
- With steplessly adjustable, vibration-proof, ergonomic auxiliary handle, for optimum handling and machine control
- Guard with pivoting segment to allow grinding right up to the wall. Height-adjustable to the disc height and for optimum dust extraction
- Adapter for FLEX Clip -on system as standard equipment
- 125 mm diameter, ideal for application on small or medium size wall or floor areas
- Turbo-Jet grinding disc with optimum removal rate. The wide range of diamond segments provides a considerably quieter operating performance and a more attractive sanding pattern. Ideal for surface grinding on mineral substrates.

Technical attributes	LD 18-7 125 R, Kit Turbo-Jet
Disc Ø	125 mm
No load speed	7000 rpm
Power input	1800 watt
Power output	1200 watt
Tool fixture	M 14
Weight	4,2 kg

Standard equipment	
1 Turbo-Jet grinding disc	348.899
1 dust extraction hood with brush ring	
1 handle	
3 cable clips	252188
1 hexagon socket wrench	
1 vacuum adapter	340.790
1 pin wrench	107.492
1 carry case	329.908

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Accessories

PCD grinding disc



PCD grinding disc, the new dimension for removal of thermal coatings from mineral substrates, masonry, oil-based paints and latex paints.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	359.416
-------	---	---------



Grinding disc fitted with polycrystalline diamond segments. For the removal of thermally sensitive coatings such as adhesives, sealants, plastic coatings, bitumen coatings from mineral substrates. The PCD segments enable coatings to be removed quickly and effectively without sticking.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	406.015
-------	---	---------

Diamond disc Turbo-Jet



Turbo-Jet grinding disc with optimum removal rate. The wide range of diamond segments provides a considerably quieter operating performance and a more attractive sanding pattern. Ideal for surface grinding on mineral substrates.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	348.899
-------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Screed-Jet diamond grinding disc



Sanding wheel for abrasive materials. For removal of formwork transitions and concrete runs from freshly concreted surfaces, mineral adhesives, screeds, plaster, mortar, abrasive lime sand brick, sandstone, chamotte, asphalt.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø	1	359.394
-------	---	---------

Thermo-Jet diamond grinding disc



Diamond grinding head suitable for grinding concrete parts, roughing old weathered concrete, hard cement plaster, removing shuttering protrusions and concrete runs, hardened epoxy resin coatings and the natural sintering on concrete components. High grinding capacity and service life from the innovative segment design. Optimal ground preparation for further coating.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø	1	359.378
-------	---	---------

Surface-Jet diamond grinding disc



Special sanding wheel for cosmetic treatment of concrete and removal of graffiti, as well as for removal of slight unevenness and transitions from concrete parts, soiling on concrete and hard plaster.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø	1	359.424
-------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Dust guard with pivoting edge segment



Enables you to work near edges at maximum extraction power.
Tool-free height adjustment via clamping lever allows quick adjustment of the extraction hood to the tool height.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	393.363
-------	---	---------

Diamond grinding disc



Universal sanding wheel for sanding mineral surfaces.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	420.417
-------	---	---------

Brush ring



Brush ring for dust extraction hood - contains two segment parts.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	394.076
125 Ø	3	421.138

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Renovation machines

Plastic multi-carrying case



Perfect fitting, impact resistant carrying case for L 3206 CD, L 3208 CD, L 21-6 230, L 24-6 230, LD 3206 C, SR 602 VV, SK 602 VV, LD 18-7 125, L 21-8 180.

QTY/PKG:	Order no.
----------	-----------

1	329.908
---	---------