

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
[info@flex-tools.com](mailto:info@flex-tools.com)  
[www.flex-tools.com](http://www.flex-tools.com)

**FLEX****Screwing and drilling****CHE 2-28 SDS-plus****Order no. 413.666**

Technical attributes	CHE 2-28 SDS-plus
No load speed	0-1300 rpm
Blows per minute	0-4000 bpm
Single impact energy (EPTA)	2,7 J
Max. drill hole Ø in concrete	26 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	30 mm
Power input	800 watt
Tool fixture	SDS-plus
Weight	2,65 kg

**Universal rotary hammer drill, 2,5 kg, SDS-plus**

- Light 800 watt hammer drill and chisel hammer, pistol design with the clockwise/anticlockwise rotation function
- Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- Hammer drilling
- Depth limit gauge: for precision drilling
- Rotation stop for chiselling
- Max. drilling range up to 26 mm in concrete
- Accelerator switch with lock-on function
- Ideal for drilling and hammer drilling, diameters from 4-18 mm in masonry and concrete for dowel fixings or through-holes.
- For light-duty chiselling work when removing plaster and tiles

**Standard equipment**

- |                             |
|-----------------------------|
| 1 handle                    |
| 1 drill depth stop          |
| 1 carrying case L-BOXX® 136 |
| 1 case insert               |