

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Screwing and drilling

FHE 2-22 SDS-plus

Order no. 413.674

**Rotary hammer drill, 2,3 kg, SDS-plus**

- Light-weight and handy 710 watt fixing hammer shaped like a gun
- Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- Hammer drilling
- Depth limit gauge: for precision drilling
- Max.drilling range up to 22 mm in concrete
- Accelerator switch with lock-on function
- Ideally suited for drilling/hammer drilling, diameter 4-12 mm in concrete for attachment of dowels and anchors

Technical attributes	FHE 2-22 SDS-plus
No load speed	1400 rpm
Blows per minute	4300 bpm
Single impact energy (EPTA)	2,1 J
Max. drill hole Ø in concrete	22 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	26 mm
Power input	710 watt
Tool fixture	SDS-plus
Weight	2,3 kg

Standard equipment

1 handle	
1 drill depth stop	
1 carrying case L-BOXX® 136	414.085
1 case insert	