

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Screwing and drilling

### FHE 2-22 SDS-plus

Order no. 413.674



#### Rotary hammer drill, 2,3 kg, SDS-plus

- Light-weight and handy 710 watt fixing hammer shaped like a gun
- Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- Hammer drilling
- Depth limit gauge: for precision drilling
- Max.drilling range up to 22 mm in concrete
- Accelerator switch with lock-on function
- Ideally suited for drilling/hammer drilling, diameter 4-12 mm in concrete for attachment of dowels and anchors

Technical attributes	FHE 2-22 SDS-plus
No load speed	1400 rpm
Blows per minute	4300 bpm
Single impact energy (EPTA)	2,1 J
Max. drill hole Ø in concrete	22 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	26 mm
Power input	710 watt
Tool fixture	SDS-plus
Weight	2,3 kg

#### Standard equipment

1 handle	
1 drill depth stop	
1 carrying case L-BOXX® 136	414.085
1 case insert	

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Screwing and drilling

### Accessories

#### SDS 2-plus drill

---



Drill with 2 solid carbide alloy cutters, reinforcement chamfer and centering point for easy, precision-point working. Asymmetrical, high-capacity double conveyor spirals for quick transfer of the drill dust. Core reinforcement for maximum energy transfer from hammer drill to drill tip. Vibration-damping and also conveys more energy to the cutting bit. Ideal for drilling in concrete, masonry and natural stone.

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Screwing and drilling

Diameter in mm:	Length in mm:	QTY/PKG:	Order no.
4	110	1	367.931
5	110	1	367.958
6	110	1	367.966
5	160	1	367.974
6	160	1	367.982
8	160	1	367.990
10	160	1	368.008
12	160	1	368.016
6	210	1	368.024
8	210	1	368.032
10	210	1	368.040
12	210	1	368.059
14	210	1	368.067
16	210	1	368.075
8	260	1	368.083
10	260	1	368.091
12	260	1	368.105
14	260	1	368.113
16	310	1	368.121
18	200	1	368.148
20	200	1	368.156
18	450	1	368.164
20	450	1	368.172
22	450	1	368.180
25	450	1	368.199

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Screwing and drilling

### Hammer drill bit set SDS-plus

---



Set consisting of 1 x D 5x110, 1 x D 6x110, 1 x D 8x110, 1 x D 8x160, 1 x D 10x160.

QTY/PKG:	Order no.
----------	-----------

---

1	414.026
---	---------



Drill bits with 2 main and 2 secondary cutting edges and centring tip for simple, pinpoint drilling even in reinforced concrete. With a 4-spiral drill bit shank for quicker, optimum removal of the drilling dust and to reduce the drill bit temperature.

Diameter in mm:	Length in mm:	QTY/PKG:	Order no.
-----------------	---------------	----------	-----------

---

8	250	5	414.034
---	-----	---	---------

### Quick-release drill chuck for CHE 2-26 SDS-plus

---



Diameter in mm:	QTY/PKG:	Order no.
-----------------	----------	-----------

---

1,5-13	1	272.639
--------	---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Screwing and drilling

### SDS-plus adapter

---



Adapter for 1/2" drill chuck (Order No. 272.639).

**QTY/PKG:    Order no.**

---

**1            368.652**

### SDS-plus M14 adapter

---



M 14 threaded mixer paddle adapter. Useable with SDS-plus hammer drill.

**QTY/PKG:    Order no.**

---

**1            374.091**

### Helix paddle WR2

---



Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.

**Paddle in    Mix in kg:    QTY/PKG:    Order no.**  
**mm:**

---

**120 Ø        15-25        1            368.989**

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Screwing and drilling

### Beater RB

---



Round mixing arms prevent air bubbles from being mixed in. Ideal for all materials where air pockets are to be avoided: filler compounds, fillers, adhesives, sealants.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
---------------	------------	----------	-----------

---

120 Ø	-15	1	369.144
-------	-----	---	---------

### Drill dust adapter

---



The drill dust extractor is connected to the suction hose of the FLEX vacuum cleaners or to different adapters so that the dust is extracted directly through the drill hole. There is no dust residue. For drilling applications up to Ø 24 mm.

Dimensions in mm:	QTY/PKG:	Order no.
-------------------	----------	-----------

---

290 x 65	1	394.025
----------	---	---------

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Screwing and drilling

### Carrying case L-BOXX®



The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXX®es optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.

External dimensions x W x H:	Internal dimensions x W x H:	Weight:	QTY/PKG:	Order no.
442 x 357 x 151	378 x 311 x 107	2,2	1	414.085

### Insert for carry case

Matching insert for CHE 2-28/FHE 2-22 SDS plus for carry case L-BOXX® 136.

QTY/PKG:	Order no.
1	414.042

### Grid foam insert L-BOXX®



Grid foam insert for the L-BOXX® type 136. The perforated foam allows the foam insert to be individually adjusted to the contents.

QTY/PKG:	Order no.
1	419.370

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Screwing and drilling

### Trolley L-BOXX®

---



Trolley for the L-BOXX®es made of plastic with 4 castors, two of which can be locked. Can be loaded up to 100 kg.

<b>Dimensions</b>	<b>Weight:</b>	<b>QTY/PKG:</b>	<b>Order no.</b>
-------------------	----------------	-----------------	------------------

in mm:

---

<b>646 x 492 x</b>			
<b>182</b>	<b>3,8</b>	<b>1</b>	<b>419.400</b>