FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



## 2600 watt angle grinder T-Rex with enormous reserves of power, 230 mm

## L 26-6 230

## Order number 436.704



## 2600 watt angle grinder T-Rex with enormous reserves of power, 230 mm

- + Microprocessor control with soft start, restart protection after power failure, overload protection, CDC-electronic feedback control
- + Anti-Kickback this shuts down the motor on the disc being blocked
- + Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- + Highly efficient and resilient motor for more power output
- + An additional vibration damping ring between the motor housing and rear handle reduces the vibrations.
- + SoftVib handgrip for reduced vibration can be mounted in three positions.
- + Rear shaft handle with soft padding for secure grip. The grip area turns 90° to the right and left for an optimum working position
- + Spindle lock
- + Removable covering cap for easy change of carbon brushes
- + Tool-free adjustment of safety guard
- + Cutting guard, optional accessory (order no. 389.625)

Technical attributes	
Max. disc diameter	230
No load speed	6500
Power input	2600
Power output	1800
Tool fixture	M 14
Clamping collar Ø	64
Cable length	4,0
Weight	6,35

Standard equipment	
1 guard grinding 230 Ø	338.729
1 SoftVib handle	325.384
1 pin wrench BL 5	100.110
1 clamping flange	338.753
1 hexagon socket wrench, SW 6	104.167
1 SDS-Clic quick-clamp nut M 14	253.049