FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



# 1010 watt 2-speed mixer with accelerator trigger switch

## MXE 1002 + WR2 120

### Order number 433.209



Technical attributes	
No load speed 1st gear	0-530
No load speed 2nd gear	0-780
Power input	1010
Power output	550
Tool fixture	M 14
Clamping collar Ø	53
Max. mixing paddle Ø	120
Size (WxLxH)	405 x 215 x 340
Cable length	4,0
Weight (without mixing paddle)	4,6

### 1010 watt 2-speed mixer with accelerator trigger switch

+ Large, rugged 2-gear unit with optimum ratios for powerful torque and correct speed for different materials

+ Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges

+ On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station

+ The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches

+ Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation

+ Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site

+ Protective cap above the motor housing guides the cooling air flow and prevents the ingress of rain water

+ Spindle lock with start-up protection. Simplifies exchange of the mixing paddle

+ For mixed applications up to 40 kg

+ Universal mixer for practically all construction materials: the 2nd gear provides it with exceptional sustained power in the top and low speed range

+ With mixing paddle for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...

### Standard equipment

1 WR2 helix paddle 120x600 M14	368.881	
1 open-ended wrench SW 22	109.398	