FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Roto random orbit polisher

XFE 7-15 150



Roto random orbit polisher

+ VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection

- + Free-spinning drive for hologram-free finishing
- + 15 mm orbit for high efficiency
- + Continuous speed control trigger: for a gentle start and a lock-on for continuous operation
- + Cushioned special hook and loop pad for polishing.
- + Counterweight for smoother operation

+ Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user

+ Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.

+ Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.

+ Low heat generation on the surface makes it ideal for temperature-sensitive paints

Order number 418.080

Technical attributes	
No load speed	1500-4500
Max. polishing pad diameter	160
Max. back-up pad diameter	150
Orbit	15
Orbit rate, no load	2900-8600
Power input	710
Power output	420
Size (L x H)	370 x 140
Cable length	4,0
Weight	2,4

Standard equipment

1 special velcro backing	437.077
pad, 150 Ø	