



ISC L-1625 Top

Order no. 018577



Equipment

- Automatic impulse filter cleaning cleans the filters during suction operation - without air flow interruption for permanent operation!
- New high-performance turbine with better suction power
- · Power socket with automatic ON/OFF
- Stepless speed controller
- Filter indicator light
- · Soft start control & tracking electronics
- · Water level detection with sensor shutdow
- · Antistatic preparation
- · Cable hook for cable storage
- · Tube fixation by Velcro tape
- · Accessories storage
- Robust, double-walled container suitable for construction sites
- Large, reinforced wheels and castors, flush, stable locks
- New rotary slide: Easy handling facilitates the flexible use of fleece and PE bags.
- **New container** closure for dust-free transport
- · Storage surface for tools and small parts

IFA-certified vacuum cleaner for slightly hazardous dusts of dust class L, dust retention capacity 99 %.

Dust-free and therefore healthier working!

More safety in the workplace!

Technical Data

Power consumption max.	1600 Watt
Air flow max.	75 l/s*
Vacuum max.	280 mbar*
Sound pressure level	69 dB(A)
Container capacity (max.) I Gross-dust-water	25 l; 20 l; 15 l;
Dimensions (L × W × H) (incl. push handle)	45 cm x 39 cm x 49 cm
Weight	12,2 kg
Power cord length	8 m (rubber, H05RR-F), red
Operating range	13,0 m – 14,0 m
* Measured at the motor head	

Scope of Supply

EWS accessory set consisting of:

- 1 x Suction hose (Ø 35 mm x 5 m)
- 1 x Stainless steel handle pipe with auxiliary air slide
- 2 x Stainless steel suction pipe (50 cm each)
- 1 x Crevice nozzle (22 cm)
- 1 x Connection sleeve (stepped)
- 1 x Dust nozzle 37 with hard floor insert
- 1 x Fleece filter bag FBV 25/35
- 1 x Velcro tape
- 2 x folded filter cassettes FKP 4800 M Adv. Polyester (dust class M, ≥ 99,9%)

