

FT

Timber Frame Wall Tie

FT-50

Tested Values

	Compression (kN)	Y_m	Tension (kN)	Y_m
Nail end (as received)	1.057		0.648 (nail withdrawal)	1.3 ⁽¹⁾
(24mm movement)	0.612	1.15 ⁽³⁾ (buckling of tie – steel failure)	0.690	
Masonry end	0.954	1.15 ⁽³⁾ (buckling of tie – steel failure)	1.836 (masonry withdrawal)	3 ⁽²⁾

(1) from BS EN1995-1-1 table 2.3 connections (fixing withdrawal of tie)

(2) from NA to BS EN1996-1-1 table NA.1 (mortar failure of tie)

(3) from NA to BS EN1995-1-1 table NA.3 (steel buckling of tie)

Based on the following criteria the following calculations have been done:

In the following examples a factored windload of 1.65kN/m² is suggested

Partial factor for variable action		1.5
Combined pressure coefficient		1.1
Peak velocity pressure		= 1.0 kN/m ²
Applied wind load on gable panel	= 1.5 x 1.1 x 1.0	= 1.65 kN/m ²

Failure	Test Result (kN)	Y_m	k_{mod} *	Result x k_{mod} / Y_m (kN)
Compression	0.612	1.15	1.1	0.585
Tension	0.648	1.3	1.1	0.548
Tension	1.836	3	1.1	0.673
Compression	0.954	1.15	1.1	0.912
				0.548

*An instantaneous action (k_{mod} value – 1.1) has been used.

Maximum net surface wind pressure for the FT-50

Product Code	Vertical Tie Spacing (mm)							
	225		300		375		450	
	Stud Centres (mm)							
	600		600		600		600	
	Maximum Net Surface Wind Pressure							
	kN/m²	ties/m²	kN/m²	ties/m²	kN/m²	ties/m²	kN/m²	ties/m²
FT-50	4.05	7.4	3.01	5.5	2.41	4.4	2.02	3.7

	1000/225 = 4.4444 4.4444x(1000/600) = 7.4 ties/m ²	1000/300 = 3.3333 3.3333x(1000/600) = 5.5 ties/m ²	1000/375 = 2.6666 2.6666x(1000/600) = 4.4 ties/m ²	1000/450 = 2.2222 2.2222x(1000/600) = 3.7ties/m ²
--	--	--	--	---

Lowest failure (with Y_m & k_{mod} applied)	0.548 x 7.4 = 4.05kN/m ²	0.548 x 5.5 = 3.01kN/m ²	0.548 x 4.4 = 2.41kN/m ²	0.548 x 3.7 = 2.02kN/m ²
--	-------------------------------------	-------------------------------------	-------------------------------------	-------------------------------------

Peak velocity pressure (kN/m ²)	2.45	1.82	1.46	1.22
---	------	------	------	------

Based on the above values this could be worked backwards

Provide a maximum wind load for 3.7 ties/m² = (2.02/1.1/1.5) = 1.22kN/m² peak velocity pressure