

TECHNICAL SPECIFICATION



2m Webbing Anchorage Sling

2m Webbing Anchorage Sling / FAR0504



DESCRIPTION

2m Webbing Anchorage Sling made from 20mm wide polyester webbing. 25kN breaking strength.

OPTIONS

2m Webbing Anchorage Sling (FAR0504)

SAFETY STANDARDS

EN 795



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Length
2m



Rated Weight / Load
25kN Breaking Strength

Material
20mm Wide Polyester Webbing



Product Weight
250g

DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-far0504-far0514.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

