

TECHNICAL SPECIFICATION



Aluminium Scaffolding Hook

Aluminium Scaffolding Hook / FAR0901



DESCRIPTION

Auto closing and auto locking type aluminium scaffold hook in aluminium alloy silver. Breaking load 22kN.

OPTIONS

Aluminium Scaffolding Hook (FAR0901)

SAFETY STANDARDS

EN 362



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Material
Aluminium Alloy

Gate Opening
60mm

Product Weight
480g

Connector Type
Self Closing and Automatic Locking



Rated Weight / Load
22kN Breaking Load



DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0901.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

