

TECHNICAL SPECIFICATION



Aluminium Tower Hook

Aluminium Tower Hook / FAR0908



DESCRIPTION

Auto closing and auto locking type tower / rebar hook in aluminium alloy silver. Breaking load 20kN.

OPTIONS

Aluminium Tower Hook (FAR0908)

SAFETY STANDARDS

EN 362



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Material
Aluminium Alloy

Gate Opening
60mm

Product Weight
243g

Connector Type
Self Closing and Automatic Locking



Rated Weight / Load
20kN Breaking Load



DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0908.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

