

KOHLER®



HP 2.26 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

HONDA Professional Engine
Automatic priming
Solid and high-performance equipment
Offers accessories
High-pressure equipment

With nearly 6 bar of pressure, the HP 2.26 H can be used for high-pressure cleaning of machinery, such as agricultural vehicles. When combined with the nozzle kit, it can be used to suppress fires.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE SPECIALIST

High performance under extreme conditions.



HP 2.26 C5

GENERAL SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	High voltage use
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	440
Outflow maximum (m3/h)	26.4
Lifting height (m)	57
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Oui
Fuel	Petrol
Tank (L)	3.1
75% cons. (l/h)	0.9
75% Autonomy (h)	3.4
Sound power level guaranteed LwA dB(A)	108
Acoustic pressure level @1m in dB(A)	92
Acoustic pressure level @7m in dB(A)	77

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (l)	0.6

DIMENSIONS AND WEIGHT

Length (cm)	41.5
Width (cm)	54.5
Height (cm)	45.5
Dry Weight (kg)	30

PACKAGING

Packaging type	Box
Length (cm)	54
Width (cm)	42
Height (cm)	45
Weight (kg)	35
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	148
weight of the packaged Pallet (kg)	430

KOHLER®

\$DATEJOURS

HP 2.26 C5 - PORTABLE POWER – WATERPUMP AQUALINE SPECIALIST

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED

Inlet filter
Circlips
Screw-on connectors
User and maintenance manual

OPTIONS

- RBH1** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
- RBH0-5** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
- RHO** Cover for SDMO 's generating sets, welding sets and water pumps
- R09** Fire-fighting kit for HP 2.26 H pumpos with 2 fire hose connectors, 25 m fire hose, 5 m intake hose and fire lance